

HWD9888(62)TSD
NEO Series Hotel Cordless Phone



Intelligent Communication Device for Next Generation Network



HWD9888(62)TSD

NEO Series Hotel Cordless Phone

NEO's Ultra thin design by Internationally renowned design firm, easily complements today's modern guestroom. Its small footprint makes managing the desk space easy. The optional high powered mobile device charger provides guests with convenient USB Charging and the patented MCC (Multi Connector Charging) allows your guest to charge their devices with multiple charging head options.

The battery backup supplies and in the case of power loss. The LED status indicator eliminates the guess work of the battery backups condition.



iMulti-function Base with USB charging

Highlights:

- Small, Sleek, Versatile and Very Functional.
- Full Duplex Speakerphone on base & handset
- Two high powered USB charge ports (optional)
- Patented Multi Function Connectors provide Apple Lighting Connector, Apple Legacy 30 pin Connector, Micro USB Connector for any Android, Blackberry, etc (optional)
- Automatic handset registration
- Streamlined Power & Line Cord Integration
- Power failure (lifeline) mode
- Battery backup (optional)
- ProGard Keyboard: Our unique internal keyboard design provides far greater reliability than conventional designs
- Redials the last number dialed. Dialed number disappears within 5 minutes for guest privacy
- Multiple colors optional for different hotel interior designs.
- Portrait and landscape format optional for different hotel decoration needs.

Main Features:

- Supports Auto and manual handset registration
- Handsets warn of low battery, and recharge rapidly.
- Five step adjustable ringer volume on both the base unit and handset.
- Supports up to 4 additional cordless handsets
- Redials the last number dialed. Dialed number disappears within 5 minutes for guest privacy
- Automatic handset registration
- Dynamic transmit power minimizing handset battery drain
- Up to 10 programmable guest service buttons on the base
- Compatible with all major hotel PBX message waiting formats
- Up to 3 programmable guest service buttons on the handset
- Full length faceplate for hotel's logo and dialing instructions
- Desk or wall mountable
- Low battery indicator
- HAC feature

HWD9888(62)TSD

NEO Series Hotel Cordless Phone

Specifications

CHARACTERISTICS	
Phone Type	<ul style="list-style-type: none"> Analog Cordless
Flash Time	<ul style="list-style-type: none"> 100ms, 300ms, 600ms optional
RAM	<ul style="list-style-type: none"> EEPROM
Phone Keys	<ul style="list-style-type: none"> 10 service keys: MUTE, HOLD, Volume+/-, FLASH, REDIAL, SPKR, (CONF, LINE1, LINE2 Only for two-line version) Phone Keys 12 Dialing Buttons (0~9, *, #), Message Waiting Lamp(MWL) Up to 3 service keys on the handset
I/O Interfaces	<ul style="list-style-type: none"> 2 RJ11 ports
RF Options	<ul style="list-style-type: none"> 2402.784 MHz-2480.544 MHz 1899.072 MHz-1902.528 MHz(Standard)
Transmission	<ul style="list-style-type: none"> RF Transmission Power : < 100 mW (Adjustable) RF Access Method and Modulation : GMSK RF Impendency : 50 ohm Test Environment, horizontal distance: 100m Dynamic Transmit Power in accordance with distance
Battery	<ul style="list-style-type: none"> Up to 7 days of standby 8 hours of talk time Power: 2.4V/600mAh Battery Hibernation Mode Durning Transportation
Package Info	<ul style="list-style-type: none"> Size: 46*37*24cm 12 Set/Carton

Call Features	<ul style="list-style-type: none"> 2 lines (Optional) Auto Answer 3-way Conference(Only for two-line version) Call Hold Call Forwarding Call Mute Call Pickup MWI Full-duplex Speakerphone Redial Volume adjustment- handset/hand free/speaker/ringing
Special Features	<ul style="list-style-type: none"> Supports use of Bittel cloning programmer to quickly and easily program speed dial keys with digital accuracy. Automatic Handset Synchronization: Handsets automatically synchronize with the base simply by placing handset on base and charging. Multiple Remote Handset Support up to 4 Slave handsets
Phone feature	<ul style="list-style-type: none"> iMulti-function model supports Apple iDevices charging as well as other phones.(Optional) Phone base can make or receive calls without external power. Compatible with all major PBX brand Support up to 4 remote handsets Full length faceplates for hotel name/logo and dialing instructions Flat handset available in optional color, (black, red, silver and orange) Automatic Handset Synchronization
Environmental	<ul style="list-style-type: none"> Operation Temperature: 0~50 Degree C Storage Temperature: -25~ 85 Degree C Relative Humidity: 10%~90% No Condensing
Power	<ul style="list-style-type: none"> DC Adaptor: 9V/1A Output :220V
Size	<ul style="list-style-type: none"> Upright Model: 19.3cm(L)*11cm(W)*10.1cm(H) Low-profile Model: 20.4cm(L)*11cm(W)*8.7cm(H)
Weight	<ul style="list-style-type: none"> 950g (No packet)



Bittel Intelligent Technology Co., Ltd

ADD: No.1 Rizhao N Road, Rizhao, China 276800

International Business:

Tel: +86-633-2212177

Fax: +86-633-2212118

E-mail: info@bittelgroup.com

Website: www.bittelgroup.com

www.bittelphone.com